



# Tanker Couplings


## Aluminium Storz Couplings

- Sizes:** 1/2" to 8"
- Materials:** Aluminium Alloy  
Optional Materials of Stainless Steel and Brass available
- Pressure:** Maximum working pressure 16 bar/232 psi
- Options:** Both halves of the coupling are of an identical design with no separate male or female halves. Either half can, therefore, be connected to any similar size of coupling. The hose coupling can be connected to another style, e.g.: hose tail, female or male threaded and blanking caps. It is essential that the distance between locking ears (KA) is the same on all fittings



SUCTION COUPLINGS				
PART NO.	NOMINAL SIZE	D (mm)	KA (mm)	L (mm)
2/D-25 AL	Storz 25 (D) = DIN 14301	25	31	50
2/32-19 AL	Storz 32	19	44	65
2/32-25 AL	Storz 32	25	44	65
2/32-32 AL	Storz 32	32	44	75
2/38-38 AL	Storz 38	38	52	75
2/C-32 AL	Storz 52 (C)	25	66	90
2/C-38 AL	Storz 52 (C)	32	66	90
2/C-45 AL	Storz 52 (C)	45	66	90
2/C-52 AL	Storz 52 (C) = DIN14321	52	66	90
2/C-60 AL	Storz 52 (C)	60	66	125
2/65-65 AL	Storz 65	65	81	90
2/B-65 AL	Storz 75 (B)	65	89	125
2/B-70 AL	Storz 75 (B)	70	89	95
2/B-75 AL	Storz 75 (B) = DIN 14322	75	89	125
2/B-80 AL	Storz 75 (B)	80	89	135
2/90 AL	Storz 90	90	105	150
2/100 AL	Storz 100	100	115	120
2/A-100 AL	Storz 110 (A)	100	133	170
2/A-110 AL	Storz 110 (A) = DIN 14323	110	133	170
2/125 AL	Storz 125	125	148	196
2/135-135 AL	Storz 135	135	159	196
2/150-150 AL	Storz 150 = F (3 Claws) Forged	150	160	180
2/165-150 AL	Storz 165	150	188	275
2/205 AL	Storz 205	205	220	375
96	Storz Spanner	-	-	-


Rubber Seals (suitable for Petrol and Oil Fluids)



## BSPF FEMALE THREADED ADAPTERS

PART NO.	NOMINAL SIZE DIN ISO 228	PIPE THREAD	KA (mm)	MATERIAL
3/D-050 AL	Storz 25 (D) - DS*	1/2"	31	Aluminium Alloy
3/D-075 AL	Storz 25 (D) - DS*	3/4"	31	Aluminium Alloy
3/D-100 AL	Storz 25 (D) - DS* = DIN14306	1"	31	Aluminium Alloy
3/32-100 AL	Storz 32 - DS*	1"	44	Aluminium Alloy
3/32-125 AL	Storz 32 - DS*	1 1/4"	44	Aluminium Alloy
3/38-150 AL	Storz 38 - DS*	1 1/2"	52	Aluminium Alloy
3/38-200 AL	Storz 38 - DS*	2"	52	Aluminium Alloy
3/C-100 AL	Storz 52 (C)	1"	66	Aluminium Alloy
3/C-125 AL	Storz 52 (C)	1 1/4"	66	Aluminium Alloy
3/C-150 AL	Storz 52 (C)	1 1/2"	66	Aluminium Alloy
3/C-200 AL	Storz 52 C = DIN14307	2"	66	Aluminium Alloy
3/C-250 AL	Storz 52 (C)	2 1/2"	66	Aluminium Alloy
3/65-200 AL	Storz 65	2"	81	Aluminium Alloy
3/65-250 AL	Storz 65	2 1/2"	81	Aluminium Alloy
3/B-200 AL	Storz 75 (B)	2"	89	Aluminium Alloy
3/B-250 AL	Storz 75 B = DIN 14308	2 1/2"	89	Aluminium Alloy
3/B-300 AL	Storz 75 (B)	3"	89	Aluminium Alloy
3/90-300 AL	Storz 90	3"	105	Aluminium Alloy
3/100-400 AL	Storz 100 - DS*	4"	115	Aluminium Alloy
3/A-400 AL	Storz 110 (A)	4"	133	Aluminium Alloy
3/A-450 AL	Storz 110 A = DIN 14309	4 1/2"	133	Aluminium Alloy
3/125-500 AL	Storz 125	5"	148	Aluminium Alloy
3/150-600 AL	Storz 150 = F (3 Claws) Forged	6"	160	Aluminium Alloy
3/165-600 AL	Storz 165	6"	188	Aluminium Alloy
3/165-700 AL	Storz 165	7"	188	Aluminium Alloy
3/205-800 AL	Storz 205	8"	220	Aluminium Alloy
96	Storz Spanner	-	-	-

\*DS - Suitable for both pressure and suction couplings




## BSPM MALE THREADED ADAPTERS

PART NO.	NOMINAL SIZE DIN ISO 228	PIPE THREAD	KA (mm)	MATERIAL
4/D-100 AL	Storz 25 (D) - DS*	1"	31	Aluminium Alloy
4/D-32-100 AL	Storz 32 DS*	1"	44	Aluminium Alloy
4/32-125 AL	Storz 32 DS*	1 1/4"	44	Aluminium Alloy
4/38-150 AL	Storz 38 - DS*	1 1/2"	52	Aluminium Alloy
4/C-125 AL	Storz 52 (C)	1 1/4"	66	Aluminium Alloy
4/C-200 AL	Storz 52 (C)	2"	66	Aluminium Alloy
4/B-250 AL	Storz 75(B)	2 1/2"	89	Aluminium Alloy
4/B-300 AL	Storz 75(B)	3"	89	Aluminium Alloy
4/A-400 AL	Storz 110(A)	4"	133	Aluminium Alloy


\*DS - Suitable for both pressure and suction couplings

# Tanker Couplings




## REDUCERS STORZ - STORZ (SWIVEL)

PART NO.	NOMINAL SIZE	KA x KA (mm)	MATERIAL
7/C-D AL	C - D = DIN 14341	66/31	Aluminium Alloy
7/B-C AL	B - C = DIN 14342	89/66	Aluminium Alloy
7/A-B AL	A - A = DIN 14343	133/89	Aluminium Alloy



## REDUCERS STORZ - STORZ (RIGID)

PART NO.	NOMINAL SIZE	KA x KA (mm)	MATERIAL
7/C-38 AL	Storz C-38	66/52	Aluminium Alloy
7/C-32 AL	Storz C-32	66/44	Aluminium Alloy
7/65-C AL	Storz 65-C	81/66	Aluminium Alloy
7/B-65 AL	Storz B-65	89/81	Aluminium Alloy
7/90-B AL	Storz 90-B	105/89	Aluminium Alloy
7/100-B AL	Storz 100-B	115/89	Aluminium Alloy
7/A-100 AL	Storz A-100	133/115	Aluminium Alloy
7/125-A AL	Storz 125-A	148/133	Aluminium Alloy
7/150-A	Storz 150-A	160/133	Aluminium Alloy



## BLANK CAPS WITH CHAIN

PART NO.	NOMINAL SIZE	KA (mm)	MATERIAL I.D. of coupling
8/D AL	Storz 25 D - DS* = DIN 14310	31	Aluminium Alloy
8/32 AL	Storz 32 DS*	44	Aluminium Alloy
8/38 AL	Storz 38 DS*	52	Aluminium Alloy
8/C AL	Storz 52 C = DIN 14311	66	Aluminium Alloy
8/65 AL	Storz 65	81	Aluminium Alloy
8/B AL	Storz 75 B = DIN 14312	89	Aluminium Alloy
8/90 AL	Storz 90	105	Aluminium Alloy
8/100 AL	Storz 100 - DS*	115	Aluminium Alloy
8/A AL	Storz 110 A = DIN 14313	133	Aluminium Alloy
8/125 AL	Storz 125	148	Aluminium Alloy
8/150 AL	Storz 150 = F (3 Claws) forged	160	Aluminium Alloy
8/165 AL	Storz 165	188	Aluminium Alloy
8/205 AL	Storz 205	220	Aluminium Alloy
96	Storz Spanner	-	-

\*DS - Suitable for both pressure and suction couplings



DELIVERY-SUCTION SEALS	
PART NO.	NOMINAL SIZE
69/D PB	Storz 25 D* = DIN 14301
69/32 PB	Storz 32 - DS*
69/38 PB	Storz 38 - DS*
69/CPB	Storz 52 C = DIN 14311
69/65 PB	Storz 65
69/BPB	Storz 75 B = DIN 14312
69/90 PB	Storz 90
69/100 PB	Storz 100 - DS*
69/A PB	Storz 110 A = DIN 14313
69/125 PB	Storz 125

\*DS - Suitable for both pressure & suction couplings.  
Food quality material available on request.