

Bayco Bayonet Style Dry Disconnect Couplings

Application: Bayonet dry disconnect fittings are ideally suited for the spill-less transfer of petroleum products such as fuel oil, lube oil blending, and tank truck delivery. The design of the Bayco bayonet dry disconnect system ensures a spill free connection, fluid cannot flow until couplings are connected together and the valve is opened. The coupling can then not be disconnected until the valve handle is closed.

Standards: Manufactured to interchange with other brands of bayonet type dry disconnect couplings. Canadian registration number CRN #OH14055 all provinces.

Materials: Adapters have anodized aluminium *, brass * or stainless steel * bodies with either anodized aluminium * or brass * poppet valves. Couplers are aluminium. Adapters and couplers are available with either buna or FKM seals.

- Features & Benefits:**
- Helps eliminate the possibility of costly spills
 - Compatible with most other brands of bayonet style dry disconnects
 - Female NPT
 - Rubber dust caps and plugs with stainless steel chains are available to protect the adapters and couplers from contamination and damage
 - Maximum operating pressure: 85 PSI at 75°F, for pressure ratings at other temperatures contact Dixon™.

* Dependent upon part #, see part number list below for more details



BA32-200



BA62-300

FEMALE NPT ADAPTERS

PART NO.	RUBBER DUST CAP PART NO.	DESCRIPTION	FEMALE NPT SIZE	SEAL MATERIAL
BA31-200	BAC-200	Stainless steel body with brass poppet valve	2"	Buna
BA32-200	BAC-200	Stainless steel body with brass poppet valve	2"	FKM
BA31-300	BAC-300	Brass body and poppet valve	3"	Buna
BA32-300	BAC-300	Brass body and poppet valve	3"	FKM
BA61-300	BAC-300	Anodized aluminium body and poppet valve	3"	Buna
BA62-300	BAC-300	Anodized aluminium body and poppet valve	3"	FKM

See pages 118-121 for repair kits and replacement parts.

Product instruction sheets and technical data can be viewed on our website at dixoneurope.co.uk

Tanker Couplings



BC61-200



BSS61-300



BS61-300

FEMALE NPT COUPLERS

PART NO.	RUBBER DUST CAP PART NO.	DESCRIPTION	FEMALE NPT SIZE	SEAL MATERIAL
BC61-200	BPC-200	Anodized aluminium body with straight non-swiveling NPT connection	2"	Buna
BC62-200	BPC-200	Anodized aluminium body with straight non-swiveling NPT connection	2"	FKM
BSS61-200	BPC-200	Aluminium body with straight swiveling NPT connection	2"	Buna
BSS62-200	BPC-200	Aluminium body with straight swiveling NPT connection	2"	FKM
BS61-200	BPC-200	Aluminium body with 90° swiveling NPT connection	2"	Buna
BS62-200	BPC-200	Aluminium body with 90° swiveling NPT connection	2"	FKM
BSS61-300	BPC-300	Aluminium body with straight swiveling NPT connection	3"	Buna
BSS62-300	BPC-300	Aluminium body with straight swiveling NPT connection	3"	FKM
BS61-300	BPC-300	Aluminium body with 90° swiveling NPT connection	3"	Buna
BS62-300	BPC-300	Aluminium body with 90° swiveling NPT connection	3"	FKM

Bayco Bayonet Style Dry Disconnect Caps and Plugs

Application:

Bayonet dry disconnect caps and plugs keep dirt, debris and water out of couplers preventing build up on the sealing surface that will cause seals to fail prematurely.

Materials:

The caps have a stainless steel chain to secure them to the adapter chain lug. The plugs have a stainless steel chain to secure them to the coupler.

Features & Benefits:

- Simple to use
- Low cost
- Durable and flexible rubber
- Prevents contamination of product



BAC-300



BCP-300

PART NO.	SIZE	DESCRIPTION
BPC-200	2"	Coupler plug
BPC-300	3"	Coupler plug
BAC-200	2"	Adapter cap
BAC-300	3"	Adapter cap