

## DELVAC - PVC Suction & Delivery Hose



Technical Characteristics	
Application	Low pressure generic hose for water and dilute chemicals. For use in agriculture, construction and water utility industries
Construction	Transparent Green PVC according to EU10/2011
Branding	DIXON DELVAC
Reinforcement	PVC spiral helix
Temperature	-10°C TO +55°C
Safety Factor	3:1

Sizes						
I.D (mm)	O.D (mm)	Max Working Pressure (Bar)	Min Burst Pressure (Bar)	Vacuum	Min Bend Radius (mm)	Weight (Kg/Mtr)
19	25	8	24	0.7	86	0.28
25	32	6.5	19.5	0.7	114	0.33
32	39	5.5	16.5	0.7	143	0.46
38	45	4.5	13.5	0.7	171	0.55
51	60	4.5	13.5	0.7	230	0.81

## IRRIBULK - PVC Suction & Delivery Hose



Technical Characteristics	
Application	Medium Duty hose for water, slurry, abrasives and chemicals. For use in agriculture, construction and civil engineering industries
Construction	Olive Green PVC according to EU10/2011
Branding	DIXON IRRIBULK M
Reinforcement	PVC spiral helix
Temperature	-10°C TO +55°C
Safety Factor	3:1

Sizes						
I.D (mm)	O.D (mm)	Max Working Pressure (Bar)	Min Burst Pressure (Bar)	Vacuum	Min Bend Radius (mm)	Weight (Kg/Mtr)
25	32	8	24	0.78	57	0.36
32	39	7	21	0.78	72	0.46
38	46	6.3	19	0.78	86	0.57
51	60	5.3	16	0.78	114	0.83
63	73	5	15	0.78	143	1.05
76	86	4.3	13	0.78	171	1.47
102	113	4	12	0.78	284	2.17
152	166	3.3	10	0.6	401	4.22

All Hose Assemblies compliant with Pressure Equipment Directive 2014/68/EU

We reserve the right to change hose specifications without prior notice