Dixon® Fire Submittal Sheet, Long Handle Aluminum Adapters



Long Handle Aluminum Adapters



SFSA4045F-LH

NOTE: All adapters rated for **175 PSI** standard working pressure unless otherwise stated and shipped with washers if needed.

NOTE: When ordering, the layout will follow (side 1 x side 2)

Side 1 Size & Thread Options

Nominal Size	Thread
3/4"	NST
1"	NPSH
1-1/2"	NPT
2"	GHT
2-1/2"	NYFD
3"	BCT (British Columbia)
3-1/2"	QST (Quebec Standard)
4"	CSA (Canadian Standard)
4-1/2"	WCT (Western Canada)
5"	NS1 (Nova Scotia)
6"	Cam & Groove
	Storz
	Other

Specifications

- ☐ Black anodized 6061-T6 Aluminum; Reducers
- ☐ Black anodized 6061-T6 Aluminum; Increasers
- ☐ Black anodized 6061-T6 Aluminum; Same Size

Layout

- ☐ Female Long Handle Swivel x Male
- ☐ Female Long Handle Swivel x Female
- Double Female Long Handle Swivel
- ☐ Storz x Female Long Handle Swivel
- ☐ Female Cam & Groove x Male
- ☐ Female Cam & Groove x Female
- ☐ Male Cam & Groove x Male
- ☐ Male Cam & Groove x Female

Side 2 Size & Thread Options

Nominal Size	Thread
3/4"	NST
1"	NPSH
1-1/2"	NPT
2"	GHT
2-1/2"	NYC (New York Corp)
3"	NYFD
3-1/2"	QST (Quebec Standard)
4"	CSA (Canadian Standard)
4-1/2"	WCT (Western Canada)
5"	NS1 (Nova Scotia)
6"	BCT (British Columbia)
	Cam & Groove
	Storz
	Other

NOTE: Other local threads are available and are made to order. Ask Dixon Fire customer service for availability and lead times on combinations.

NOTE: Storz is only available in 1-1/2", 2", 2-1/2", 3", 4", 5" & 6".

Replacement gaskets, washers, and hardware are available upon request.

Dixon Fire

325 Arbor Ct Winchester, VA 22602 ph: 877.712.6179 fx: 800.283.4966 dixonvalve.com

© 2023 DVCC • AAFDC_723