Dixon® Fire Submittal Sheet Rocker Lug Aluminum Adapters



Rocker Lug Aluminum Adapters



N37-25F25F

NOTE: All adapters rated for **175 PSI** standard working pressure unless otherwise stated and shipped with washers if needed.

NOTE: When ordering, the layout will follow (side 1 x side 2)

Side 1 Size & Thread Options

Nominal Size	Thread
3/4"	NST
1"	NPSH
1-1/2"	NPT
2"	GHT
2-1/2"	NYFD
3"	BCT (British Columbia)
3-1/2"	QST (Quebec Standard)
4"	CSA (Canadian Standard)
4-1/2"	WCT (Western Canada)
5"	NS1 (Nova Scotia)
6"	Cam & Groove
	Other

Specifications

- ☐ Black anodized 6061-T6 Aluminum; Reducers
- ☐ Black anodized 6061-T6 Aluminum; Increasers
- ☐ Black anodized 6061-T6 Aluminum; Same Size

Layout

- ☐ Rigid Male x Male
- ☐ Rigid Female x Male
- ☐ Rigid Female x Female
- ☐ Female Swivel x Male
- ☐ Female Swivel x Female
- Double Female Swivel
- ☐ Female Swivel x Male w/Poly Screen
- ☐ Female Cam & Groove x Male
- ☐ Female Cam & Groove x Female
- ☐ Male Cam & Groove x Male
- ☐ Male Cam & Groove x Female

Side 2 Size & Thread Options

Nominal Size	Thread
3/4"	NST
1"	NPSH
1-1/2"	NPT
2"	GHT
2-1/2"	NYC (New York Corp)
3"	NYFD
3-1/2"	QST (Quebec Standard)
4"	CSA (Canadian Standard)
4-1/2"	WCT (Western Canada)
5"	NS1 (Nova Scotia)
6"	BCT (British Columbia)
	Cam & Groove
	Other

NOTE: Other local threads are available and are made to order. Ask Dixon Fire customer service for availability and lead times on combinations.

Replacement gaskets, washers, and hardware are available upon request.

Dixon Fire

325 Arbor Ct Winchester, VA 22602 ph: 877.712.6179 fx: 800.283.4966 dixonvalve.com

© 2023 DVCC • AAFDC_723