# Dixon® Fire Submittal Sheet Brass Rocker Lug Adapters





RHA25T25F

## **Rocker Lug Hydrant**

### **Specifications**

- ☐ Cast and/or forged brass; reducers
- ☐ Cast and/or forged brass; increasers
- Cast and/or forged brass; same size

NOTE: All adapters rated for **175 PSI** standard working pressure and include washers if needed.

### Layout

- ☐ Rigid Male x Male
- ☐ Rigid Female x Male
- ☐ Female Swivel x Male
- ☐ Female Swivel x Female
- Double Female Swivel
- ☐ Female Swivel x Male w/ Poly Screen
- ☐ Female Swivel x Female w/ Poly Screen

NOTE: When ordering, the layout will follow (side 1 x side 2)

# **Side 1 Size & Thread Options**

# Side 2 Size & Thread Options

<b>Nominal Size</b>	Thread	<b>Nominal Size</b>	Thread
3/4"	NST	3/4"	NST
1"	NPSH	1"	NPSH
1-1/2"	NPT	1-1/2"	NPT
2"	GHT	2"	GHT
2-1/2"	NYC (New York Corp)	2-1/2"	NYC (New York Corp)
3"	NYFD	3"	NYFD
3-1/2"	QST (Quebec Standard)	3-1/2"	QST (Quebec Standard)
4"	CSA (Canadian Standard)	4"	CSA (Canadian Standard
4-1/2"	WCT (Western Canada)	4-1/2"	WCT (Western Canada)
5"	NS1 (Nova Scotia)	5"	NS1 (Nova Scotia)
6"	BCT (British Columbia)	6"	BCT (British Columbia)
	Other		Other

NOTE: Other local threads are available and are made to order. Ask Dixon Fire customer service for availability and lead times on combinations.

Replacement gaskets/washers are available upon request.

### **Dixon Fire**

325 Arbor Ct Winchester, VA 22602 ph: 877.712.6179 fx: 800.283.4966 dixonvalve.com

© 2023 DVCC • BAFDC\_723