Boss LPS Tees and Spool Adapters

Application

 Used in the transfer of water, brine, water-based chemicals, water-based acids, and gelatinous proppant (sand) slurry used at hydraulic fracturing sites

Size

4"

Features

- · No welds or pipe threads to degrade and cause premature leakage
- Two-piece nut is pinned and bolted for perfect alignment
- · Figure 206 threads are interchangeable with other reliable brands

Materials

- Nut: forged AISI steel
- Iron

Specifications

- Working pressure: 1000 PSI
- Iron adapter meets ASTM standards
- · Forged steel nut meets AISI standards
- Additional configurations are available, contact Dixon® for details

Tees1

Part #	Description
HUFMM2064T	female x male x male tee
HUFMF2064T	female x male x female tee
HUMMM2064T	male x male x male tee
HUFFF2064T	female x female x female tee
HUMMF2064T	male x male x female tee
HUFFM2064T	female x female x male tee

Spool Adapters¹

Part #	Description
HUFMT206441T	male x female spool adapter with 1" side port
HUFM206400SA	male x female spool adapter
HUMMT206441T	male x male spool adapter with 1" side port
HUFFT206441T	female x female spool adapter with 1" side port
HUMM206400SA	male x male spool adapter
HUFF206400SA	female x female spool adapter
HUFT206400SA	4" female x male NPT spool adapter
HUMT206400SA	male x male NPT spool adapter
HUFTT206441T	female x male NPT spool adapter with 1" side port
HUMTT206441T	male x male NPT spool adapter with 1" side port

¹ Nuts are included with male end configurations





Elbows



HU206 elbows are available in 4" with 45°, 60°, 80°, and 90° options; ends can be configured (male x male, female x female, male x female, etc.) to customers' requirements.

Flange Assemblies



Assemblies (specific adapter, plug/cap, chain, etc.) can be tailored to customer requirements.

Caps, Plugs, and Nuts



Caps, plugs, nuts, chains, retaining rings, shackles, and bolts are available, as well as kits.

Size

- 2", 4", 5", 6", and 8" caps, plugs, and nuts

Flange Adapters



125# lightweight and butterfly valve flanges available in 3", 4", 6", and 8" with 45° options; ends can be configured (male and female 206 hammer union, male NPT, and grooved end; standard and short length).

Frac Hose Fittings



Size

• 1", 2", 3", 4", 5", 6", and 8"

Materials

- · Iron or stainless steel
- Schedule 40 and 80
- · Zinc plated
- Nut: forged AISI steel
- Figures 50, 100, 200, and 206 (size dependent)



Scan for additional Dixon Boss® LPS literature.